



Via Senese Romana, 45 - 50053 Empoli (FI)
+39 0571932179 - +39 3711418088 Whatsapp e Telegram
Servizio clienti: info@effebimegastore.it
Post vendita: info@effebimegastore.it
Skype: effebimegastore

[P.A. Professional Audio Live Pro](#) › [Finali di Potenza - Amplificatori](#)



Euro 0,00

Finale di Potenza Amplificatore 2 canali 900w/8 ohm, 1500w/4 ohm, con DSP e connessione Ethernet M30D DSP ETH PowerSoft

Codice: M30D DSP ETH



Marchio:

EAN/UPC: M30D DSP ETH

Confezione: Pz 1

Peso: Kg. 8

Descrizione

Finale di Potenza Amplificatore 2 canali 900w/8 ohm, 1500w/4 ohm, con DSP e connessione Ethernet M30D DSP ETH PowerSoft

Generale Numero canali 2 Potenza d'uscita Single channel mode Distributed line* Bridge mode 4 ? 8 ? 70V 100V 8 ? 1500 W 900 W 1200 W 1500 W 3000W Tensione massima / corrente di picco 135 Vpeak / 65 Apeak 100 Vpeak 140 Vpeak 270 Vpeak Alimentazione CA Alimentazione Universal, regulated switch mode Tensione operativa 100-240 V $\pm 10\%$, 50-60 Hz Tensione di funzionamento 90 V - 264 V Consumo energetico** 115 V 230 V Idle 37 W 0.6 A 37 W 0.3 A 1/8 potenza massima @ 4 ? 530 W 7 A 530 W 3.54 A 1/4 potenza massima @ 4 ? 1024 W 13.04 A 1024 W 6.52 A Caratteristiche termiche Range di temperatura operativa 0° - 45° C - 32° - 113° F Dissipazione termica** 115 V 230 V Idle 126 BTU/h 31.8 kcal/h 126 BTU/h 31.8 kcal/h 1/8 potenza massima @ 4 ? 529 BTU/h 133.3 kcal/h 529 BTU/h 133.3 kcal/h 1/4 potenza massima @ 4 ? 935 BTU/h 235.6 kcal/h 935 BTU/h 235.6 kcal/h Audio Guadagno 32dB, 30dB, 28dB, 26dB, 24dB, 22dB, 20dB, 18dB, 14dB, 4dB, -, user selectable Sensibilità d'ingresso 2.13 V / 8.8 dBu Livello massimo di ingresso 6 V / 17.7 dBu Risposta in frequenza 20 Hz - 20 kHz (± 0.5 dB) @ 1 W, 8 ? Rapporto segnale/rumore > 108 dB (20 Hz - 20 kHz, A weighted) Separazione Crosstalk > 70 dB @ 1kHz THD+N 0.08% @ 1/2 full power IMD 0.02% Impedenza d'ingresso 10 k Ω balanced Slew rate 40 V/?s @ 8?, input filter bypassed Fattore di smorzamento > 5000 @ 100 Hz DSP Architettura DSP Analog Devices ADAU® 1701 DSP Convertitore A/D Cirrus Logic CS 5381, 2 channel, 24 bit @ 48 kHz, 120 dB S/N Convertitore D/A Cirrus Logic CS 4398, 2 channel, 24 bit @ 48 kHz, 120 dB S/N Precisione interna Fixed point Firmware Network upgradable firmware Latenza 0.644 ms fixed latency architecture Equalizzatore ingresso up to 5 biquad IIR filters (PEQ, shelving, band pass, band stop, all pass) Equalizzatore uscita 16 fully parametric filters per channel, IIR: peaking, hi/lo-shelving, hi/lo-pass, band-pass, band-stop, all-pass. Custom FIR up to 384 taps @ 48 or 96 kHz Crossover Butterworth, Linkwitz-Riley, Bessel: 6 dB/oct to 48 dB/oct Delay 340 ms input delay plus 10 ms per output Limiters Peak limiter, RMS limiter, frequency dependent RMS limiter Controllo di smorzamento < 120 Hz, range ± 2 ? Pannello anteriore Indicatori e comandi 1 x LED - Status 1 x LED - Over-temperature protection 2 x LED bar - Signal level + CLIP 2 x Knob - Level

attenuator (stepped) 1 x Power switch - Connettori AC main 1 x IEC C14 connector - 15 A max (region-specific power cord provided) Audio signal input 2 x XLR - Signal input Auxiliary voltage 1 x 2 pin Phoenix MC 1.5/2-ST-3.81 - External voltage connector (DSP version only) Audio out (link through) 2 x XLR - Signal output (link through) Loudspeakers 2 x speakON - Neutrik NL4MD Network/data 1 x Rj45 socket - RS485 data connection (non-DSP version) Costruzione
Dimensioni (L x H x P) 483 mm x 44.45 mm x 358 mm (19.0 in x 1.8 in x 14.1 in) Peso 7.4 kg (16.3 lb)

© 2024 EffeBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213