



Via Senese Romana, 45 - 50053 Empoli (FI)
+39 0571932179 - +39 3711418088 Whatsapp e Telegram
Servizio clienti: info@effebimegastore.it
Post vendita: info@effebimegastore.it
Skype: effebimegastore

[P.A. Professional Audio Live Pro](#) › [Finali di Potenza - Amplificatori](#)



Euro 0,00

Finale di Potenza Amplificatore 4 canali 600w/8 ohm, 600w/4 ohm 2404 PowerSoft

Codice: 2404



Marchio:

EAN/UPC: 2404

Confezione: Pz 1

Peso: Kg. 8

Descrizione

Finale di Potenza Amplificatore 4 canali 600w/8 ohm, 600w/4 ohm 2404 PowerSoft

Generale Numero canali 4 Potenza d'uscita Single channel mode Distributed line* Bridge mode 2 ? 4 ? 8 ? 70V 100V 4 ? 8 ?

800 W 600 W 600 W 600 W 1600W 1200W Tensione massima / corrente di picco 100 Vpeak / 45 Apeak

Alimentazione CA Alimentazione Universal, regulated switch mode with PFC (Power Factor Correction) Tensione operativa

100-240 V $\pm 10\%$, 50-60 Hz Tensione di funzionamento 90 V - 264 V Consumo energetico** 115 V 230 V Idle 31.4 W 0.40

A 31.6 W 0.28 A 1/8 potenza massima @ 4 ? 442 W 4.2 A 438 W 2.39 A 1/4 potenza massima @ 4 ? 878 W 8.02 A 849 W

4.41 A Caratteristiche termiche Range di temperatura operativa -10° - 45° C - 14° - 113° F Dissipazione termica** 115 V 230

V Idle 107.2 BTU/h 27.0 kcal/h 107.9 BTU/h 27.2 kcal/h 1/8 potenza massima @ 4 ? 484.8 BTU/h 122.2 kcal/h 471.2 BTU/h

118.7 kcal/h 1/4 potenza massima @ 4 ? 949.1 BTU/h 239.2 kcal/h 850.1 BTU/h 214.2 kcal/h Audio Risposta in frequenza 20

Hz - 20 kHz (± 0.5 dB) @ 1 W, 8 ? Rapporto segnale/rumore > 108 dB (20 Hz - 20 kHz, A weighted) Separazione Crosstalk >

70 dB @ 1kHz THD+N 0.1% from 0.1 W to full power (typically 500 @ 20-100 Hz DSP Convertitore A/D 24 Bit Tandem™

@ 48 kHz 125 dB-A Dynamic Range - 0.005 % THD+N Convertitore D/A 24 Bit Tandem™ @ 48 kHz 125 dB-A Dynamic

Range - 0.005 % THD+N Precisione interna 32 bit floating point Memoria/Presets 128 MB (RAM) plus 512 MB flash for

presets / Latenza 2.5 ms fixed latency architecture Equalizzatore ingresso Raised-cosine, custom FiR, parametric iIR: peaking,

hi/lo-shelving, all-pass, band-pass, band-stop, hi/lo-pass Crossover linear phase (FIR), Butterworth, Linkwitz-Riley, Bessel: 6

dB/oct to 48 dB/oct (IIR) Delay 2 s (input) + 100 ms (output) for time alignment Equalizzatore d'ingresso Equalizzatore

d'uscita Limiters TruePower™, RMS voltage, RMS current, Peak limiter Controllo di smorzamento Active

DampingControl™ and Liveimpedance™ measurement Pannello anteriore Connettori AC main 1 x IEC C20 connector - 20

A max (region-specific power cord provided) Audio signal input 1 x 12 pin Phoenix MC 1.5/12-ST-3.81 - Signal input -

MAIN Alarm 1 x 12 pin Phoenix MC 1.5/12-ST-3.81 - Alarm connector 1 x 4 pin Phoenix MC 1.5/4-ST-3.81 - Alarm

connector Loudspeakers 1 x 8 pin Phoenix DFK-PC 4/8-G-7.62 - Signal output Network/data 1 x RJ45 socket - RS485 data

connection (non-DSP version) 1 x RJ45 socket - DANTE® Costruzione Dimensioni (L x H x P) 483 mm x 44.45 mm x 360

mm (19.0 in x 1.8 in x 14.2 in) Peso 7 kg (15.4 lb)

© 2024 EffeBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213