Via Senese Romana, 45 - 50053 Empoli (FI)
+39 0571932179 - +39 3711418088 Whatsapp e Telegram
Servizio clienti: info@effebimegastore.it
Post vendita: info@effebimegastore.it
Skype: effebimegastore

Euro 1299,00

SUBWOOFER ATTIVO 12'' 2000W QSC KS112 - 6 ANNI DI GARANZIA + SPEDIZIONE OMAGGIO

Codice: KS112

Marchio:

Descrizione
SUBWOOFER ATTIVO 12" 2000W QSC KS112 - 6 ANNI DI GARANZIA + SPEDIZIONE OMAGGIO

SUBWOOFER ATTIVO 12" 2000W QSC KS112 + SPEDIZIONE OMAGGIO

Il KS112 è un subwoofer amplificato ultracompatto, ideale per le installazioni fisse e i sistemi portatili nelle applicazioni di intrattenimento. Il KS112 è un subwoofer passa-banda facilmente trasportabile, dotato di un singolo altoparlante da 12 pollici, con un modulo di amplificazione da 2000 Watt di picco in Classe D. La cassa è costruita in legno di betulla di alta qualità e include delle ruote a basso rumore di trascinamento.

L'unità offre due inserti filettati M20 per un'installazione stabile e sicura su asta di supporto, sia in verticale che in orizzontale (asta di supporto non inclusa).

Caratteristiche

- Elevato livello di uscita in un fattore-forma ultracompatto
- Modulo di amplificazione da 2000 Watt in Classe D
- Altoparlante da 12 pollici a lunga escursione; design passa-banda del 6° ordine
- Intrinsic Correction™ per la taratura e la gestione dei diffusori
- L'aspetto raffinato e professionale è ideale in qualsiasi applicazione
- Cassa in legno verniciato ultraresistente, a garanzia di una durata prolungata di esercizio
- Installazione in posizione verticale o orizzontale grazie al doppio inserto filettato M20

- Placca di protezione KS-LOC opzionale, che consente l’accesso ai controlli solo al personale autorizzato
- Informazioni EASE e CAD disponibili online
- **6 anni di garanzia**

SPECIFICATIONS	KS112
Configuration	6th-Order Bandpass Subwoofer
LF Transducer	12-inch (305 mm), Cone
Frequency Response (-6 dB)	41 Hz - 108 Hz
Frequency Range (-10 dB)	38 Hz - 121 Hz
Maximum Rated SPL1	128 dB @ 1 m (peak)
Amplifier	Class D 2000W (peak)
Cooling	Low-noise, variable speed fan
Controls	Power On/Off Gain Control Rotary encoder 2 x selection buttons
Indicators	2 x Power LED (front and rear) Input Signal LED Limiter Active LED
Connectors	2 x locking XLR/F 1/4-inch combo 2 x XLR/M (Loop-thru Output) 1 x locking IEC power connector
AC Power Input	Universal power supply 100 - 240 VAC, 50 - 60 Hz
AC Power Consumption	100 VAC, 2.4 A / 120 VAC, 2.0 A / 240 VAC, 1.3 A
Enclosure Details	
Enclosure	15 mm Birch Plywood
Color	Black (RAL 9011)
Grille	Internal woofer cover
Dimensions (HWD) inches	24.5 x 15.5 x 24.25
Dimensions (HWD) mm	622 x 394 x 616
Net Weight	28.4 kg (62.6 lbs)
Shipping Weight	34.5 kg (76 lbs)
Regulatory	CE, WEEE, UL, China RoHS, RoHS II, FCC Class B
Included Accessories	4 x Low-Noise, Heavy Duty Casters
Optional Accessories	KS112 CVR Transport Cover, KS-LOC Lock-Out Cover SP-16X Extension Pole, SP-36 Extension Pole

1 Peak SPL is measured on-axis at 1m, pink noise crest factor 10dB, unweighted Continuous SPL is based on theoretical calculations based upon transducer sensitivity and peak available power (for comparison purpose and in accordance with common industry practice.

With product registration. Visit QSC.com for full details

All specifications are subject to change without notice.

© 2024 EffeBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213