



Vi
- 5
+ 3
37
e'
Se
in
Pe
in
Sk

[Altoparlanti - Membrana - Recone Kit - Bordi](#) > [Altoparlanti - Woofer - Speakers](#) > [10" Pollici 25 Cm](#)

E

Al
W
25
O
Pr

C

M



E
FI

C

Pe

Image: ALTOPARLANTE WOOFER 10" Pollici 25 Cm 150 Watt 4 Ohm 10FE200C Faital Pro 10 FE 200 C

Descrizione

ALTOPARLANTE WOOFER 10" Pollici 25 Cm 150 Watt 4 Ohm 10FE200C Faital Pro 10 FE 200 C

Nominal Specifications Nominal Diameter 10", 250 mm Overall Diameter 10.1", 256.8 mm Bolt Circle Diameter 9.6", 243.8 mm Diameter 9.2", 233.8 mm Depth 4", 102 mm Flange and Gasket Thickness 0.31", 8 mm Electrical Specifications Minimum Impedance 4 Ohm Nominal Power Handling*** 150 W Maximum Power Handling**** 300 W Sensitivity (1W/1m) 90 dB Range 50 - 4,500 Hz Voice Coil Diameter 1.45", 37 mm Winding Material Aluminium Former Material Kapton Winding Depth 0.31", 8 mm Flux Density 1 T THIELE & SMALL Parameters Resonant Frequency (fs) 55 Hz DC Resistance (BL) 8.2 N/A Diaphragm Mass inc. Airload (Mms) 24.4 grams Mechanical Compliance of Suspension (Cms) 0.3 mm/N Electromagnetic Q (Qes) 0.9 Mechanical Q (Qms) 12 Total Q (Qts) 0.8 Compliance Equivalent Volume (Vas) 1.52 ft³, 43.3 dm³ (Sd) 49.8"², 321.3 cm² Maximum Linear Excursion (Xmax)* 4.7 mm Xdamage** 10.4 mm Coil Inductance (Le) 0.42 mH Diaphragm Mass 21.14 g Eta Zero 0.95 % Notes *Xmax = [(winding depth - magnetic gap depth) / 2] + (magnetic gap depth / 3) **Maximum excursion without permanent damage ***2 Hours Test According to AES 2-1984 Rev. 2003 ****Maximum power is defined as 3dB greater than nominal

© 2024 EffeBi Megastore - Shop Exclusively Online. All Rights Reserved. P.Iva: 07989761213